BRILLUME
Refined Elegance

www.brillume.co.in

SOLEN
36

SURFACE / SUSPENDED LUMINAIRE

Engineered for refined
architectural environments.



POWER	BEAM ANGLE	LUMINOUS FLUX	CRI	UGR
36W	60°	5040 / 4860 / 4680 lm	80 / 90	< 19

APPLICATION AREAS

Office buildings | Retail | Supermarkets | Hospitality | Library

TECHNICAL SPECIFICATIONS

CONSTRUCTION & MATERIALS

Size Out Side (mm)	1085×36×70
Cut Out Size (mm)	1085×36×70
Housing	Extruded Aluminium
Lens / Diffuser	High Transmission PC
Reflector	PC High Purity Metallised
Surface Finish	White/Black/Custom Powder Coated
IP Rating	IP 30

THERMAL MANAGEMENT

Heat Sink Material	Aluminium
Cooling Technique	Passive

OPTICAL SYSTEM

Beam Angle	60°
Illumination Mode	Direct Lighting
Swivel	No

Technical parameters are subjected to change time to time
in order to improve product performance and reliability.

LIGHT TECHNOLOGY

LED Fitted	Bridgelux,Osram,Cree
Delivered Lumens	4680 / 4500 / 4320
CCT (K)	6000 / 4000 / 3000
Tunable	On Request
LED Binning	3 Step MacAdam
CRI (Ra)	80 / 90
LED Life L70	45,000 HRS
Luminaire	5040 / 4860 / 4680
Luminous Efficacy	130 Lumens / Watt


ELECTRICAL SYSTEM

(UGR)	< 19
Input Voltage	220 TO 240 Vac
Input Power	36W
Power Factor	>0.96
THD	<10%
Control Gear	Remote
Driver Protection	OVP,Short Circuit,Surge
Dimming	Phase / Analog / Dali / RF / APP
Emergency	BACKUP On Request
Battery Backup	On Request


PACKAGING DETAILS

Packing Qty 2 **Gross Weight** - **Carton Size (L x B x H)** (LXBXH) -

DIMENSIONS (MM)



PHOTOMETRIC



Brillume Lighting Solutions Pvt. Ltd.
Office No. 87, Upper Floor,
Om Heera Panna, Oshiwara,
Andheri West, Mumbai — 400 102

+91 91674 23259

manoj@brillume.co.in