BRILLUME
Refined Elegance

www.brillume.co.in

IVOIA
60

SURFACE / SUSPENDED LUMINAIRE

Engineered for refined
architectural environments.



POWER	BEAM ANGLE	LUMINOUS FLUX	CRI	UGR
60W	110°	8400 / 8100 / 7800 lm	80 / 90	< 19

APPLICATION AREAS

Residential | Office buildings | Retail | Sports facilities | Studio | Stage | Supermarkets | Library

TECHNICAL SPECIFICATIONS

CONSTRUCTION & MATERIALS

Size Out Side (mm)	595×595×70
Cut Out Size (mm)	570×570×70
Housing	CRCA SHEET
Lens / Diffuser	High Transmission PS
Reflector	N/A
Surface Finish	WHITE POWDER COATED
IP Rating	IP 65

THERMAL MANAGEMENT

Heat Sink Material	Aluminium
Cooling Technique	Passive

OPTICAL SYSTEM

Beam Angle	110°
Illumination Mode	Indirect Lighting
Swivel	No

Technical parameters are subjected to change time to time
in order to improve product performance and reliability.

LIGHT TECHNOLOGY

LED Fitted	Bridgelux
Delivered Lumens	6000 / 5700 / 5400
CCT (K)	6000 / 4000 / 3000
Tunable	On Request
LED Binning	3 Step MacAdam
CRI (Ra)	80 / 90
LED Life L70	45,000 HRS
Luminaire	8400 / 8100 / 7800 lm
Luminous Efficacy	100 Lumens / Watt


ELECTRICAL SYSTEM

(UGR)	< 19
Input Voltage	220 TO 240 Vac
Input Power	60W
Power Factor	>0.95
THD	<10%
Control Gear	Remote
Driver Protection	OVP,Short Circuit,Surge
Dimming	Phase / Analog / Dali / RF / APP
Emergency	BATTERY BACKUP On Request
Battery Backup	Request Battery Backup


PACKAGING DETAILS

Packing Qty - **Gross Weight** - **Carton Size (L x B x H)** (LXBXH) -

DIMENSIONS (MM)



PHOTOMETRIC



Brillume Lighting Solutions Pvt. Ltd.
Office No. 87, Upper Floor,
Om Heera Panna, Oshiwara,
Andheri West, Mumbai — 400 102

+91 91674 23259

manoj@brillume.co.in