BRILLUME
Refined Elegance

www.brillume.co.in

JAXIR 2

2

RECESSED LUMINAIRE

Engineered for refined architectural environments.



POWER	BEAM ANGLE	LUMINOUS FLUX	CRI	UGR
35W	110°	3340 / 3050 lm	> 90	< 19

APPLICATION AREAS

Residential | Office buildings | Retail | Sports facilities | Studio | Stage | Supermarkets | Library

TECHNICAL SPECIFICATIONS

CONSTRUCTION & MATERIALS

Size Out Side (mm)	595 × 595 × 100 mm
Cut Out Size (mm)	595 × 595 × 100 mm
Housing	Extruded Aluminium
Lens / Diffuser	High Performance Opal PMMA Diffuser
Reflector	N/A
Surface Finish	Customize RAL avilable
IP Rating	IP40 Driver Details

THERMAL MANAGEMENT

Heat Sink Material	Aluminium
Cooling Technique	Passive

OPTICAL SYSTEM

Beam Angle	110°
Illumination Mode	Direct Lighting
Swivel	No

Technical parameters are subjected to change time to time in order to improve product performance and reliability.

LIGHT TECHNOLOGY

LED Fitted	High Performance Bridgelux LED
Delivered Lumens	3340 / 3050 lm
CCT (K)	3000K/ 4000K/ 5700K/
Tunable	3000K/ 4000K/ 5700K/
LED Binning	<3 SDCM
CRI (Ra)	> 90
LED Life L70	L70@50000h
Luminaire	3340 / 3050
Luminous Efficacy	CRI >90 Optics


ELECTRICAL SYSTEM

(UGR)	< 19
Input Voltage	220-240 VAC
Input Power	35W
Power Factor	0.95
THD	<10%
Control Gear	Recessed
Driver Protection	OVP, Short Circuit, Surge
Dimming	Phase / Analog / Dali-2 DT6 / Dali-2 DT8 / Dali+
Emergency	On Request
Battery Backup	On Request


PACKAGING DETAILS

Packing Qty	1	**Gross Weight**	-	**Carton Size (L x B x H)**	48.5" x 3.5" x 3.5"

DIMENSIONS (MM)



PHOTOMETRIC



Brillume Lighting Solutions Pvt. Ltd.
Office No. 87, Upper Floor,
Om Heera Panna, Oshiwara,
Andheri West, Mumbai — 400 102

+91 91674 23259

manoj@brillume.co.in