BRILLUME
Refined Elegance

www.brillume.co.in

UMBIA

SURFACE / SUSPENDED LUMINAIRE

Engineered for refined architectural environments.



POWER	BEAM ANGLE	LUMINOUS FLUX	CRI	UGR
15W/4ft, 20W/4ft, 25W/4ft	Diffused	3340 / 3050 lm	> 90	< 19

APPLICATION AREAS

Residential | Office buildings | Retail | Sports facilities | Studio | Stage | Supermarkets | Library

TECHNICAL SPECIFICATIONS

CONSTRUCTION & MATERIALS

Size Out Side (mm)	1200 × 50 × 25.5 mm
Cut Out Size (mm)	1200 × 50 × 25.5 mm
Housing	Extruded Aluminium
Lens / Diffuser	-
Reflector	N/A
Surface Finish	Customize RAL avilable
IP Rating	IP 40

THERMAL MANAGEMENT

Heat Sink Material	Aluminium
Cooling Technique	Passive

OPTICAL SYSTEM

Beam Angle	Diffused
Illumination Mode	Direct Lighting
Swivel	No

Technical parameters are subjected to change time to time in order to improve product performance and reliability.

LIGHT TECHNOLOGY

LED Fitted	High Performance Bridgelux LED
Delivered Lumens	3340 / 3050 lm
CCT (K)	3000K/ 4000K/ 5700K/
Tunable	3000K/ 4000K/ 5700K/
LED Binning	<3 SDCM
CRI (Ra)	> 90
LED Life L70	L70@50000h
Luminaire	3340 / 3050
Luminous Efficacy	SDL-2021


ELECTRICAL SYSTEM

(UGR)	< 19
Input Voltage	220-240 VAC
Input Power	15W/4ft, 20W/4ft, 25W/4ft
Power Factor	0.95
THD	<10%
Control Gear	Surface
Driver Protection	OVP, Short Circuit, Surge
Dimming	Phase / Analog / Dali-2 DT6 / Dali-2 DT8 / Dali+
Emergency	On Request
Battery Backup	On Request

PACKAGING DETAILS

Packing Qty	1	**Gross Weight**	-	**Carton Size (L x B x H)**	48.5" x 3.5" x 3.5"

DIMENSIONS (MM)



PHOTOMETRIC



Brillume Lighting Solutions Pvt. Ltd.
Office No. 87, Upper Floor,
Om Heera Panna, Oshiwara,
Andheri West, Mumbai — 400 102

+91 91674 23259

manoj@brillume.co.in